



\*ALUMINUM OR STEEL SPRING ASSIST  
COVERS AVAILABLE UPON REQUEST

2PC. STEEL DIAMOND PLATE TORSION  
SPRING ASSIST PARKWAY COVER,  
GALVANIZED (DESIGNED FOR 300P.S.F.)

PAINTED OR GALVANIZED  
AVAILABLE UPON REQUEST

(A) 4pc. STEEL BOLTDOWN  
TRAFFIC / PARKWAY COVER

STEEL GALVANIZED FRAME  
CAST IN CONCRETE

(B) TOP SECTION W/  
FLUSH FRAME

(C) EXTENSION SECTION

1" DIA. GROUND  
ROD KNOCKOUT

(D) BOTTOM SECTION

(4) 8"x16" K.O'S  
(2 PER SIDE WALL)

36", 42"  
or 48"

12" DIA.  
SUMP K.O

(2) 7/8" DIA.  
STEEL GALV.  
PULL IRONS

6" WALLS  
(TYP.)

(2) 20"x20" K.O'S  
(1 PER ENDWALL)

\*\*Minimun Excavation: 8'-0"x10'-0"xDepth Req'd

**6'-0" X 8'-0" CLOSED BOTTOM  
FLATWALL PULL BOX W/  
STANDARD COVERS**

**Notes:**

1. Traffic Covers Are Designed For AASHTO H-20 Wheel Loading, But Are Not Intended For Direct Traffic Installations.
2. Parkway Covers Are Designed For A Live Load of 300 p.s.f.